

Compound element or finished part with a matt surface

A polyester film is laminates onto a decor coated wooden compound panel. The degree of gloss is < 1. The maximum coating width is 1250 mm and the maximum panel length 3050 mm. The coating is UV stabil, and is given a protective film. Pianovo Lackmatt also offers a high level of scouring resistance. The advantages: Less damage when processing and installing furniture elements. In addition to supplying panel goods for customer processing, we also offer a high quantity of attractive colors and decors as finished items with edging in matching and contrasting colours.



Standard dimensions:

Panel manufacturer	Dimensions	
Egger	2800 X 1030 mm	1250 X 2070 mm
Pfleiderer	2655 X 1030 mm	1250 X 2100 mm
Finsa	2880 X 1220 mm	
Thickness:	10 / 18,5 / 25 mm	
Foil thickness:	75 µ + protective film	

Other dimensions and manufacturers on request!
Other materials have to be tested first!

Properties:

Mechanical properties	Testing standard	Unit	Class / value
Chemical stress	DIN EN 68861 T1	Level	1B
Scratch resistance	DIN EN 68861 T4	Stufe N	4B 2,5 N
Dry heat	DIN EN 68861 T7	Level °C	7A 180°C
Moist heat	DIN EN 68861 T8	Level °C	8A 100°C
Paint adhesion	DIN EN ISO 2409	GT 0-5	GT 0
Shock loading	EN 438-2	N	9N
Light fastness	EN 438-2	Grey scale Blue scale	4-5 6
Micro scratches	DIN EN 16094 – procedure A	Change in degree of gloss in %	>30 % <50 %
	DIN EN 16094 – procedure B	Level	MRS-B3

Test	Description	Result
Aging	30 days 50 °C	passed
Distortion (in-house)	10 cycle -2,5 °C - 24 h. RT - 24 h.	passed
Uprising heat	50 °C - 1 h. 60 °C - 1 h. 70 °C - 4 h. 80 °C - 1 h.	passed
Resistance to alternating climate	AMK Modul 4	passed
Asientest (in-house)	810 h -10°C – +35°C 0% - 95% humidity	passed

Tolerances	Panel			Finished part		
Substrate	< 15 mm	15 - 20 mm	> 20 mm	< 15 mm	15 - 20 mm	> 20 mm
Thickness	± 0.5 mm			± 0.5 mm		
Length and width	± 5.0 mm			± 0.5 mm		
Distortion length/width	Concave: 1.5 mm/m convex : 1.5 mm/m Carriers <16 mm may have higher levels of distortion					
Edge defects	≤ 10 mm			Not permitted		

Thickness tolerance = nominal size + 0.2 mm (film + adhesive) ± tolerance


Surface properties	Panel	Finished part
Scratches	The named properties are assessed in accordance with DIN EN 14322, DIN EN 438-1 and AMK-MB-004	
Contrasting points		
blisters, indentations, filings under the film		
Pressure points		
Blisters		
Shade	Minor variations in line with standard commercial tolerances may occur as the result of irregularities in the coating papers and the type of carrier used	
	Permitted variations:	
	White and light colours	Delta E ≤ 0.5
	Medium colours	Delta E ≤ 0.8
	Dark colours	Delta E ≤ 1.5

Larger variations are permitted on pearlescent and metallic decors

Due to the differing shape and size of the metallic pigments used, colour effects ranging from light to dark and iridescent may occur depending on the angle of light and the angle of observation. This is part of the charm of metallic decors, and does not constitute grounds for complaint.

Distance of observation and light source as per AMK-MB-004 in the current version!

- position: installed situation
- light: fluorescent tube with 6.500°K (diffuse light or D65 light)
- angle of view: 30° to vertical
- distance: 700 mm
- Viewing time: Max. 20 seconds



The current versions of the relevant standards of guidelines for the particular materials will apply where alternative criteria are not further specified!

Cleaning recommendations:

To clean the surfaces, you need nothing other than a soft cloth and warm water with a few drops of detergent or glass cleaner. After cleaning, it is important to wipe dry with a soft cloth, preferably a microfibre cloth.

Stains, particularly those caused by strongly dyed substances and liquids, as well as splashes of fat etc., must be removed with plenty of water, if necessary adding a quantity of ordinary, non-abrasive household cleaner. After cleaning, remove any soap residue with lukewarm water and rub dry with a chamois leather. Stains should not be allowed to dry. It may no longer be possible to remove dried-on substances or substances that have been allowed to penetrate over a prolonged period of time.

Particularly stubborn stains can be removed using ordinary plastic cleaner or glass cleaner. Before applying, it is advisable to test the cleaning product on a non-visible area first.

For this reason, do not apply any abrasives, furniture polish, floor wax, cellulose and synthetic-resin thinners, acetone or similar cleaning products. Do not use steel wool or sponge scourers either!

Packing and postage:

Compound elements are usually supplied with foam sheets between the layers. Items are delivered on disposable pallets. The finished stacks are wrapped in stretch film to protect them against dirt and moisture.

Other packaging may be agreed on enquiry!

Over / under deliveries

Over / under deliveries of 10% per item for technical reasons are permitted.

General information:

Niemann Pianovo Lackgloss & Lackmatt surfaces are supplied with a protection film, which is resistant up to 80°C.

The protection film must be removed at the latest six months after delivery otherwise surface defects may arise.

Compound materials are used in decorative interior design and furniture construction. Panels are to be used in dry areas.

Careful checks of incoming goods are part of our excellent order processing sequence. They comply with the Terms and Conditions of Niemann-Möbelteile. Compound panels must be transported and stored carefully. If necessary, storage may be on a level, horizontal, dry base. In order to prevent the edges from swelling and the panels from distorting in moisture, they should be stored in a closed building. The panels should not be stored at temperatures under 15°C for long periods of time. This may result in irreversible damage (distortion) to the compound. Relative humidity should be between 45 and 65%.

This information is based on our current knowledge, and is not intended to assure any properties.

It is for information purposes only, and is not intended to assure any particular product properties or suitability for a specific purpose. Users are to ensure that our products are suitable for their particular application. This applies both for first-time samples of a product and for changes to current products. As we have no influence over the various materials and processing conditions used by our suppliers, we are unable to accept any responsibility for the information provided here. The recipients of our products are responsible for ensuring that current legislation and definitions are observed. Subject to technical amendment.

Our General Terms and Conditions apply